

PRE SEALED PAVING

ProtectiT PR is a water based fluoro polymer sealer designed to prevent dirt, oil and other contaminants from adhering to the surface of the concrete block paving. ProtectiT PR is manufactured to ISO-9001 Quality Management System / 14001 Environmental Management System

The sealing of concrete block paving, adds value, extends product life and reduces servicing frequencies and intensity.

FACTORY IN-LINE SEALING

The ideal time to apply these surface treatments is at the point of manufacture.

Paving is sealed in the factory while product is clean thus avoiding on site contamination of dirt. This allows for more accurate application of the surface treatment, ensuring that the correct amount of sealer is applied to the surface.

In turn this gives the treated surface all the properties of post impregnated paving .

It also removes the probability of secondary efflorescence and makes the application of cement based grouts easier.

BENEFITS

- Very high performance stain resistance
- Easier and faster to clean
- Reduced maintenance costs.
- Extends aesthetic value
- Improved resistance to moss and algae
- Reduced adherence of chewing gum to a algae, on the paving block sealed surface
- Substantial benefits in a rigid bedding system - it is easier to remove high strength jointing mortar from a pre-sealed surface
- Reduces occurrence of efflorescence
- ISO-9001 Quality Management System / 14001 Environmental Management System
- VOC - (Volatile organic compound), free
- Chemically inert
- Completely UV stable. Invisible protection does not alter the surface of sealed surface

TECHNICAL DATA:

- **Chemical Composition:** Aqueous fluouopolymer dispersion.
- **Density:** 1.0kg/ lt @ 250C
- **Chemical Resistance:** Mild acids and alkalis, water and deicing salts.
- **VOC Content:** 0.0g/litre