



## UNIT 28. SECOND AVE TEL: (01) 424 2070 COOKSTOWN IND. EST. EMAIL: info@chmltd.ie TALLAGHT, D24, IRELAND WEB: www.chmltd.ie

RIGHT © 2023 RAWING AND ANY DESIGN HEREON IS THE COPYRIGHT OF CHIN PAND MUST NOT BE REPRODUCED WITHOUT THEIR WRITTEN

BY A TEMPORARY TRAFFIC OPERATIONS SUPERVISOR (TTOS) WHO MUST CARRY OUT A SITE RISK ASSESSMENT TO MODIFY (IF NECESSARY) THE MEASURES DESCRIBED TO SUIT ACTUAL SITE CONDITIONS BEFORE IMPLEMENTATION.

2) THE TTOS MUST BE IN POSSESSION OF THE VALID 2) THE FIGS MOST BEINT SOCIED OF THE VALUE OF THE CONSTRUCTION SKILLS REGISTRATION CARD SIGNING, LIGHTING, AND GUARDING AT ROADWORKS' CONSTRUCTION REGULATIONS 2006 AND 2013-2021 CONSTRUCTION REGULATIONS.

3) THE TTOS TO DETERMINE EXACT POSITION OF SIGNS CONSIDERING THE SITE SPECIFICS.

OF THE CONSTRUCTION REGULATIONS (2013-2021) ARE MET, THE PSCS MUST ADVICE THE PSDP AND ALL RELEVANT PARTIES OF ANY CHANGE TO THE TEMPORARY TRAFFIC MANAGEMENT PLAN.

5) ALL WORKS ARE TO BE CARRIED OUT IN ACCORDANCE WITH LOCAL AUTHORITY REQUIREMENTS AND TO BE INCLUDED IN THE SITE SPECIFIC SAFETY & HEALTH PLAN.

6) MAINTENANCE CHECKS SHOULD BE CARRIED OUT AT REGULAR INTERVALS AND IN ACCORDANCE WITH CONTRACT SPECIFICATIONS.

7) TEMPORARY SIGNS SUPPORTS OR STANDS SHOULD BE DESIGNED IN ACCORDANCE WITH SPECIFICATION TS4.

9) ALL SIGNS USED FOR THIS TRAFFIC MANAGEMENT PLAN MUST COMPLY WITH CHAPTER 8 OF TRAFFIC SIGNS MANUAL LATEST

10) WK 052 SHOULD BE USED TO INDICATE THE POSITION OF A SITE ENTRANCE AND/OR EXIT. REFER TO CH. 8 FOR USAGE. BANKSMEN TO MANAGE SITE ACCESS & EGRESS.

11) THE ABSOLUTE MINIMUM WIDTH ALLOWED FOR PEDESTRIANS

12) SAFETY BARRIERS USED FOR THIS TMP MUST COMPLY WITH TII DN-REQ-03034-1 IS EN 1317-1 e) TEMPORARY SAFETY BARRIER

LEVEL WHERE TRAFFIC RUNS ON A TEMPORARY SURFACE AND ALSO FOR CYCLE/PEDESTRIAN RAMPS WHERE THERE IS A LEVEL DISCONTINUITY AS A RESULT OF THE WORKS ON CYLE PATHS & FOOTPATHS.

14) ADDITIONAL SIGNS MAY BE USED TO COMPLEMENT THE SPECIFIC SIGNS USED AT THE ROADWORKS: WARNING SIGNS SPECIFIC SIGNS USED AT THE ROADWORKS: WARNING SIGNS - YELLOW BACKGROUND - DESCRIBED IN CHAPTER 6, REGULATORY SIGNS - DESCRIBED IN CHAPTER 5, ETC. THEY ALL MUST COMPLY WITH THE SPECIFICATIONS OF 'TRAFFIC SIGNS MANUAL' AND 'TS4: GUIDELINES, CERTIFICATION SCHEME AND SPECIFICATION FOR CONSTRUCTION OF TRAFFIC SIGNS'.

CHAPTER 8 ROAD LEVEL: 50km/h ROADWORKS TYPE: NUMBER OF SIGNS: 50m DISTANCE BETWEEN SIGNS: 20m SIGNS SIZE RECTANGULAR - MIN.: 600mm SIGNS SIZE CIRCULAR - MIN.: 600mm CONE HEIGHT - MIN.: 750mm TAPER CONE SPACING: N/A ONGITUDINAL CONE SPACING: N/A RATE OF TAPER: N/A N/A JNOBSTRUCTED WIDTH: N/A MAXIMUM LENGTH OF SHUTTLE: N/A MINIMUM LANE WIDTH: N/A **KEY PLAN** SITE LOCATION



## SITE SPECIFIC NOTES

- FINAL VMS MESSAGE AND LOCATION TO BE
- VMS TO BE PROTECTED WITH PEDESTRIAN

**LEGEND** 

- TEMPORARY TRAFFIC SIGN - PRIMARY DIVERSION ROUTE - SECONDARY DIVERSION ROUT - TRAFFIC CONES

DATE BY F DESCRIPTION



## GLENAGEARY ROAD UPPER ACTIVE TRAVEL SCHEME

**KEY PLAN** 

BE RR CHECKED: MC NTS DRAWN BY: TM DATE: 16/03/23 CONSTRUCTION DRAWING NO: EN 6669 - 000 - 001