

# Licence to use the Irish Standard Mark

on or in connection with

Concrete: Specification,
Performance, Production and
Conformity

to indicate conformity to

I.S. EN 206:2013+A2:2021

# Roadstone Ltd

Plant 200, Belgard, Fortunestown Dublin 24

The NSAI, in exercise of the power conferred on it by subsection (1) of Section 21 of the National Standards Authority Act (No. 28 of 1996) hereby grants a licence to use the Irish Standard Mark on or in connection with Concrete - Specification, Performance, Production and Conformity (Consisting of I.S. EN 206:2013 and the Irish National Annex, 2015) to indicate conformity to I.S. EN 206:2013+A2:2021 to the above mentioned company.

An Irish Standard Mark Licence authorises the Licensee to use the Irish Standard Mark, in conjunction with the relevant Irish Standard number, on a product which is the subject of a licence, and which conforms to the relevant Irish Standard Specification. The licence is not assignable, and shall remain in force until revoked by, or surrendered by the licensee to, the NSAI.

Approved by:
Kevin D. Mullaney

Licence Number: 1.63.114
Date of issue: 20 December 2007
Revision date: 19 September 2024
Expiry date: 31 October 2025

This certificate is subject to annual revision

All valid certifications are listed on NSAI's website - <u>www.nsal.ie</u>. The continued validity of this certificate may be verified under "Certified Company Search"



NSAI (National Standards Authority of Ireland), 1 Swift Square, Northwood, Santry, Dublin 9, Ireland T +353 1 807 3800 E: <a href="mailto:info@nsai.ie">info@nsai.ie</a> www.nsai.ie www.nsai.ie NSAI Inc. 20 Trafalgar Square, Nashua, New Hampshire, NH 03063, USA T +1 603 882 4412 E: <a href="mailto:info@nsaiinc.com">info@nsaiinc.com</a> www.nsaiinc.com

# Certificate of Conformity of the Factory Production Control 1029 – CPR – GB23/0000361



In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Aggregates for concrete, described in annex.

placed on the market under the name or trade mark of

#### Roadstone Ltd

Fortunestown, Belgard, Dublin, Ireland

and produced in the manufacturing plant

## **Roadstone Ltd**

Fortunestown, Belgard, Dublin, Ireland

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard(s)

### EN 12620:2002+A1:2008

under system 2+ are applied and that the factory production control is assessed to be in conformity with the applicable requirements

This certificate is valid from 23 October 2023 until 22 October 2026

and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body.

Issue 1. Certified with SGS since 23 October 2023

Organization certified since 21 December 2018 and first certified by SGS on 23 October 2023.

Authorised by

Luis Neves

Certification Management

Authorised by Luis Santos

Certification Management

SGS ICS - Serviços Internacionais de Certificação, Lda, Notified Body 1029

Polo Tecnológico de Lisboa, Rua Cesina Adães Bermudes, lote 11, nº 1, 1600-604 Lisboa – Portugal

 $t + 351\ 217104200\ Email: pt.info@sgs.com - www.sgs.pt$ 

Pac acreditação

> C0001 ISO/IEC 17065 Produtos

This document is an authentic electronic certificate for Client' business purposes use only. Printed version of the electronic certificate are permitted and will be considered as a copy. This document is issued by the Company subject to SGS General Conditions of certification services available on Terms and Conditions | SGS. Attention is drawn to the limitation o liability, indemnification and jurisdictional clauses contained therein. This document is copyright protected and any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful.



# Certificate of Conformity of the Factory Production Control 1029 – CPR – GB23/0000361



Annex 1

Product(s): Aggregates for concrete.

Aggregate Designation (d/D*)			
*d and D in mm			
20/40			
10/20			
6.3/14			
4/10			
2/14			
2/10			
2/6.3			
0/40			
0/31.5			
0/20			
0/10			
0/6.3			











# **DECLARATION OF PERFORMANCE**

# **Aggregates for use in Concrete and Concrete Masonry Units**

## **Belgard**

1. Unique identification code of the product type:

Code	Description	Category
1571001	20/40mm	GC 85/20
1571002	20/31.5mm	G <sub>C</sub> 85/20
1571003	10/20mm	G <sub>C</sub> 85/20
1571005	6.3/14mm	G <sub>C</sub> 85/20
1571007	4/10mm	G <sub>C</sub> 85/20
1571008	2/6.3mm	G <sub>C</sub> 85/20
1570002	0/4mm (CP)	$G_A85/G_{TC}20 - G_F85$

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

Production details can be traced via dispatch docket.

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

I.S. EN 12620: Aggregates for Concrete S.R16: 2016 Guidance on the use of EN 12620

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Roadstone Ltd. Fortunestown Dublin 24

- 5. Not Applicable
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+

7. Notified certification body:

SGS (identification No. 1029) performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of constancy of conformity of the factory production control.

#### 8. Declared Performance

Characteristic	Declared Performance	Harmonised Technical Specification
Apparent Density	2.82Mg/m3	I.S. EN 1097
S.S. Dry Density	2.78Mg/m3	I.S. EN 1097
Oven Dry Density	2.76Mg/m3	I.S. EN 1097
Fines Content (Coarse agg)	F4	I.S. EN 933
Fines Content (Fine agg)	F16	I.S. EN 933
Flakiness Index (NA 2/6.3mm&0/4mm)	FI <sub>15</sub>	I.S. EN 933-3
Methylene Blue Value	MB <sub>1</sub>	I.S. EN 933-9
Water Absorption	0.5%	I.S. EN 1097
Percentage crushed and broken	C <sub>100/0</sub>	I.S. EN 933-5
Resistance to fragmentation	LA <sub>20</sub>	I.S. EN 1097-2
Resistance to Polishing Wear/Attrition	PSV <sub>44</sub>	I.S. EN 1097-8
Resistance to Abrasion	AAV <sub>10</sub>	I.S. EN 1097-8 Annex A
Resistance to Wear	M <sub>DE</sub> 25	I.S. EN 1097-1
Resistance to freezing and thawing	MS <sub>18</sub>	I.S. EN 1367-2
Drying Shrinkage	0.036%	I.S. EN 1367-4
Total Sulfur	S <sub>1</sub>	I.S. EN 1744-1
Durability against Alkali-Silica reactivity	Non-reactive	
Sulphate Content (Acid Soluble)	AS <sub>0.2</sub>	I.S. EN 1744-1
Chloride Content (Water Soluble)	0.001%	I.S. EN 1744-1
Rock Type	Limestone	

**9.** The performance of the product identified in points 1 and 2 conforms with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of Roadstone Ltd.

#### Signed for and on behalf of the manufacturer by:

Alan Lowe, Technical Director, Roadstone Ltd.

(Name and Function)

Belgard, 2/01/2025 (Place and Date of Issue)

Alan lowe



# Roadstone Ltd. Fortunestown Dublin 24 Certification Body SGS 1029 RL DoP-C-BD-01

## I.S. EN 12620: Aggregates for Concrete

Characteristic	Declared Performance
Apparent Density	2.82Mg/m3
S.S. Dry Density	2.78Mg/m3
Oven Dry Density	2.76Mg/m3
Fines Content (Coarse agg)	F4
Fines Content (Fine agg)	F16
Flakiness Index (NA 2/6.3mm&0/4mm)	FI <sub>15</sub>
Methylene Blue Value	MB <sub>1</sub>
Water Absorption	0.5%
Percentage crushed and broken	C <sub>100/0</sub>
Resistance to fragmentation	LA <sub>20</sub>
Resistance to Polishing Wear/Attrition	PSV <sub>44</sub>
Resistance to Abrasion	AAV <sub>10</sub>
Resistance to Wear	M <sub>DE</sub> 25
Resistance to freezing and thawing	MS <sub>18</sub>
Drying Shrinkage	0.036%
Total Sulfur	S <sub>1</sub>
Durability against Alkali-Silica reactivity	Non-reactive
Sulphate Content (Acid Soluble)	AS <sub>0.2</sub>
Chloride Content (Water Soluble)	0.001%
Rock Type	Limestone

Page 3 of 3 RL.DOP-C-BD-01