

NSAI, 1 Swift Square, Northwood, Dublin 9, Ireland, D09 A0E4

Certificate of conformity of the factory production control, 0050 - CPR - 0766

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product(s):

Aggregates for concrete

Placed on the market under the name of:

Roadstone Ltd Ballygarvan, Co. Cork

and produced in the manufacturing plant:

Roadstone Ltd Ballygarvan, Co. Cork

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard:

I.S. EN 12620:2002+A1:2008

under system 2+ are applied and that

the factory production control is assessed to be in conformity with the applicable requirements

This certificate was first issued on 7 March 2018 and remains valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified factory production control certification body.

File Number: Approval Date: Last Amended Date: 1.129.102 7 March 2018 27 May 2024 31 October 2025 Signed:

Mr. Kevin D. Mullaney
Director of Certification, NSAI



Expiry Date:

All valid NSAI certifications are listed on NSAI's website - <u>www.nsai.ie</u>. The continued validity of this certificate may be verified under "Certified Company Search"





DECLARATION OF PERFORMANCE

Aggregates for use in Concrete and Concrete Masonry Units

Ballygarvan

1. Unique identification code of the product type:

Code	Description	Category
1571002	20/31.5mm	Gc 85/20
1571003	10/20mm	Gc 85/20
1571005	6.3/14mm	Gc 85/20
1571007	4/10mm	Gc 85/20
1571008	2/6.3mm	Gc 85/20
1570002	0/4mm (CP)	G _A 85/G _{TC} 20 - G _F 85

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

Production details can be traced via dispatch docket.

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

I.S. EN 12620: Aggregates for Concrete

S.R16: 2016 Guidance on the use of EN 12620

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Roadstone Ltd.

Fortunestown

Dublin 24

- 5. Not Applicable
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+

7. Notified certification body:

NSAI (identification No. 0050) performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of constancy of conformity of the factory production control.

8. Declared Performance

Declared Performance	Harmonised Technical Specification
2.70Mg/m3	I.S. EN 1097
2.78Mg/m3	I.S. EN 1097
2.69Mg/m3	I.S. EN 1097
F4	I.S. EN 933
F16	I.S. EN 933
MB ₁	I.S. EN 933-9
0.4%	I.S. EN 1097
C _{100/0}	I.S. EN 933-5
LA ₃₀	I.S. EN 1097-2
AAV ₁₅	I.S. EN 1097-8 Annex A
M _{DE} 20	I.S. EN 1097-1
MS ₁₈	I.S. EN 1367-2
0.02	I.S. EN 1367-4
S ₁	I.S. EN 1744-1
Non-reactive	
AS _{0.2}	I.S. EN 1744-1
0.001%	I.S. EN 1744-1
Limestone	
	2.70Mg/m3 2.78Mg/m3 2.69Mg/m3 F4 F16 MB1 0.4% C100/0 LA30 AAV15 MDE20 MS18 0.02 S1 Non-reactive AS0.2 0.001%

9. The performance of the product identified in points 1 and 2 conforms with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of Roadstone Ltd.

Signed for and on behalf of the manufacturer by:

Alan Lowe, Technical Director, Roadstone Ltd. (Name and Function)

Belgard, 02/01/2025 (Place and Date of Issue)

Alan lowe (Signature)



Roadstone Ltd. Fortunestown Dublin 24 13 Certification Body NSAI 0050 RL DoP-C-BGVN-01

I.S. EN 12620: Aggregates for Concrete

Characteristic	Declared Performance
Apparent Density	2.70Mg/m3
S.S. Dry Density	2.78Mg/m3
Oven Dry Density	2.69Mg/m3
Fines Content (Coarse agg)	F4
Fines Content (Fine agg)	F16
Methylene Blue Value	MB ₁
Water Absorption	0.4%
Percentage crushed and broken	C _{100/0}
Resistance to fragmentation	LA ₃₀
Resistance to Abrasion	AAV ₁₅
Resistance to Wear	M _{DE} 20
Resistance to freezing and thawing	MS ₁₈
Drying Shrinkage	0.02
Total Sulfur	S ₁
Durability against Alkali-Silica reactivity	Non-reactive
Sulphate Content (Acid Soluble)	AS _{0.2}
Chloride Content (Water Soluble)	0.001%
Rock Type	Limestone