

DECLARATION OF PERFORMANCE

Aggregates for use in Bituminous Materials

Killough

1. Unique identification code of the product type:

| Code | Description | Category |
|---------|-------------------------|---------------------|
| 2920007 | 0/2mm Bituminous Filler | EN 13043 - Table 24 |

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:

Production details can be traced via dispatch docket.

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

I.S. EN 13043: Aggregates for use in Bituminous Mixtures and Surface treatments

S.R17: 2002 Guidance on the use of I.S EN 13043

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

Roadstone Ltd.

Fortunestown

Dublin 24

- 5. Not Applicable
- 6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+

7. Notified certification body:

NSAI (identification No. 0050) performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of constancy of conformity of the factory production control.

8. Declared Performance

| Characteristic | Declared Performance | Harmonised Technical Specification |
|--------------------------------|----------------------|------------------------------------|
| Particle Density | 2.67Mg/m3 | I.S. EN 1097-7 |
| Loose Bulk Density in Kerosene | 0.6Mg/m³ | I.S. EN 1097-3 |
| Total Sulfur | S ₁ | I.S. EN 1744-1 |
| Acid Soluble Sulphate | AS _{0.2} | I.S. EN 1744-1 |
| Water Soluble Chloride | <0.001% | I.S. EN 1744-1 |
| Declared Passing 2mm | 100% | 100 |
| Declared Passing 0.125mm | 90% | 85-100 |
| Declared Passing 0.063mm | 75% | 70-100 |
| Rock Type | Limestone | |

9. The performance of the product identified in points 1 and 2 conforms with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of Roadstone Ltd.

Signed for and on behalf of the manufacturer by:

Alan Lowe, Technical Director, Roadstone Ltd.

(Name and Function)
Belgard, 02/01/2025
(Place and Date of Issue)

Alan lowe



Roadstone Ltd. Fortunestown Dublin 24 Certification Body NSAI 0050 RL DoP-BF-KL-01

I.S. EN 13043: Aggregates for use in Bituminous Mixtures and Surface treatments

| Characteristic | Declared Performance |
|--------------------------------|----------------------|
| Particle Density | 2.67Mg/m3 |
| Loose Bulk Density in Kerosene | 0.6Mg/m³ |
| Total Sulfur | S ₁ |
| Acid Soluble Sulphate | AS _{0.2} |
| Water Soluble Chloride | <0.001% |
| Declared Passing 2mm | 100% |
| Declared Passing 0.125mm | 90% |
| Declared Passing 0.063mm | 75% |
| Rock Type | Limestone |

Page 3 of 3 RL.DOP-BF-KL-01