PRODUCT NAME:

AQUA RIVEN BLOCK PAVING



PRODUCT DESCRIPTION: Unique textured natural stone appearance.

PRODUCTION STANDARD: I.S. EN 1338 Concrete paving blocks — Requirements and test methods

USE: Concrete block paving for use in Sustainable Urban Paving Systems (SuDS) the Aqua Riven permeable block can be specified for all sites designed under BS7533-Pt13 and BBA certificate: 97/3373

TYPE: Permeable Concrete Block paving

FINISH/COLOUR: Brush hammered and shot blasted, tooled granite

AVAILABLE IN 2 COLOURS:

- 1. Limestone
- 2. Sandstone

AVAILABLE IN SIZES:

THICKNESS

1. 80mm for use in lightly traffic pavements, driveways, patios and footpaths.

WORKING SIZE

80mm Available in single size

• 240 x 160 x 80mm

SPECIAL SHAPES: Kerbs & Channels available to match

INSTALLATION & MAINTENANCE: Laid to BS 7533 Pt. 13 and BBA certificate: 97/3373 and technical advice given in Roadstone Brochure Technical Section. Design service available

BUILD-UP/STONE SPECIFICATION:

Lower sub-base layer 10-63mm clean crushed stone Upper sub-base layer 5-20mm clean crushed Laying course 2-6mm clean crushed stone Surface Dressing 2-4mm clean crushed stone

ANCILLARY COMPONENTS Exclusive to Roadstone / Formpave Aquaflow system

Inbitex Geotextile non-woven geotextile is used for separation, filtration and pollution control.

SC Intergrid sub-base stabilisation grid improves structural strength, increases design life and reduces construction costs.

SC Membrane This impermeable membrane allows the storage of collecting storm water. Used for the Aquaflow attenuation system it can be welded or taped dependent on the application. A higher grade SC Membrane GT can be specified when contamination is present.

SC Findrain This drainage component allows efficient and high flow removal of storm water from the Roadstone Aquaflow system. Wrapped in Inbitex Geotextile which provides further filtration and cleansing.

Aquaflow Distribution Tanks Voided crates that are extremely strong structurally and are wrapped in Inbitex

Geotextile, which provides filtration and cleansing. Allows the collection of impermeable surface water catchment, such as roofs to the Aquaflow system.

Also available from Roadstone Top Hats, Tape and Fittings